Article number: 83381510.ZW Printing possible

Mobile CB1 pallet box - 1200 x 800 x H 895 mm - 4 swivel castors - rubber tread - green

Transoplast
+31(0)314 66 44 00
webshop@transoplast.nl
transoplastshop.com

Product specifications

External (LxWxH)	1200 × 800 × 895 mm
Internal (LxWxH)	1115 × 715 × 595 mm
Capacity	475 litre
Color	Green
Sidewalls	Closed, reinforced
Material	HDPE
Article number	83381510.ZW
Weight (kg)	41,5 kg
Temperature range	-30°C to +40°C, briefly up to +90°C
Bottom	Closed, reinforced
Max. load capacity per box	600 kg
Max. static stacking load	600 kg
Max. dynamic stacking load	600 kg
Quantity per pallet	2

Features

- **Mobile plastic pallet box with runners - type CB1, dimensions 1200 x 800 x H895 mm - 470 liter**
- **Fitted with 4 galvanised swivel castors Ø 125 mm for optimum manoeuvrability**
- **Our wheels with rubber tread are shock-absorbing and low-noise. They also leave no marks on the floor**
- **With flat inner walls for quick cleaning and emptying**
- **Closed side walls, reinforced base - for safe storage and transport**
- **Very robust pallet box - widely used in all kinds of industries**
- **Equipped above the fork openings with a substantial impact zone with ribs - to prevent collision damage from forklifts**
- **The 3 pallet runners provide a particularly robust construction**
- **Emptying is possible with a forklift fitted with a rotating clamp**
- **Available in 6 colours: light grey, blue, light blue, green, red and yellow**
- **Options: lid - printing - QR codes and barcodes - 2 fixed castors and 2 swivel castors (for maximum steerability) - braked wheels - stainless steel wheels (white nylon) - coversheets**

Description

Mobile

The basis of this mobile plastic pallet box is the CB1 box - a robust pallet box with flat, smooth inner walls that are easy to clean. We have fitted this box with particularly smooth-running wheels with a rubber tread. The wheels are shock-absorbing, low-noise and leave no marks on the floor. This is why this mobile box is widely used in warehouses, along production lines and at order-picking locations.

The construction - emptying

The wheels are mounted underneath the three pallet runners of the box. These runners are moulded in one piece with the box, using the same material quality. This monoblock construction gives the box a particularly robust structure. As a result, the CB1 can be tipped easily using a forklift fitted with a rotating clamp. The flat, smooth inner walls ensure fast and efficient emptying.

Transoplast
+31(0)314 66 44 00
webshop@transoplast.nl
transoplastshop.com

Suitable accessories



83370800

Alternative articles

83281910

83281810

83281410

83281310

Transoplast
+31(0)314 66 44 00
webshop@transoplast.nl
transoplastshop.com