



Mobile CB3 pallet box - 1200 x 1000 mm - 4 swivel castors - rubber tread - blue



Product specifications

External (LxWxH)	1200 x 1000 x 895 mm
Internal (LxWxH)	1130 x 925 x 595 mm
Capacity	610 liter
Sidewalls	Closed, reinforced
Material	HDPE
Article number	83281310.ZW
Weight (kg)	43,5 kg
Temperature range	-30°C to +40°C, briefly up to +90°C
Color	Blue
Bottom	Closed, reinforced
Max. load capacity per box	600 kg
Max. static stacking load	600 kg
Max. dynamic stacking load	600 kg
Quantity per pallet	2

Features

Mobile plastic pallet box with runners - type CB3, dimensions 1200 x 1000 x H895 mm - 610 liter

Fitted with 4 galvanised swivel castors Ø 125 mm for optimum manoeuvrability

Our wheels with rubber tread are shock-absorbing and low-noise. They also leave no marks on the floor

With flat inner walls for quick cleaning and emptying

Closed side walls, reinforced base - for safe storage and transport

Very robust pallet box - widely used in all kinds of industries

Equipped above the fork openings with a substantial impact zone with ribs - to prevent collision damage from forklifts

The 3 pallet runners provide a particularly robust construction

Emptying is possible with a forklift fitted with a rotating clamp - optional stainless steel runner reinforcements are available for this purpose; for heavy-duty applications

Available in 7 colours: light grey, dark grey, blue, light blue, green, red and yellow

Options: lid - printing - QR codes and barcodes - 2 fixed castors and 2 swivel castors (for maximum steerability) - braked wheels - stainless steel wheels (white nylon) - coversheets - stainless steel runner reinforcements

Description

Mobile

The basis of this mobile plastic pallet box is the CB3 box - a robust pallet box with flat, smooth inner walls that are easy to clean. We have fitted this box with particularly smooth-running wheels with a rubber tread. The wheels are shock-absorbing, low-noise and leave no marks on the floor. This is why this mobile box is widely used in warehouses, along production lines and at order-picking locations.

The construction - emptying

The wheels are mounted underneath the three pallet runners of the box. These runners are moulded in one piece with the box, using the same material quality. This monoblock construction gives the box a particularly robust structure. As a result, the CB3 can be tipped easily using a forklift fitted with a rotating clamp. The flat, smooth inner walls ensure fast and efficient emptying.



Suitable accessories



Alternative articles

