

Article number: 52.RC682F.IWBV.2

Printing possible



Roll container - for Euronorm - 2 clamp frames, galvanised - plastic base, grey



Product specifications

External (LxWxH)	815 x 682 x 1710 mm
Internal (LxWxH)	815 x 615 x 1500 mm
Dynamic load capacity	500 kg
Article number	52.RC682F.IWBV.2
Weight (kg)	24 kg
Color	Grey
Bottom	Perforated - reinforced
Type	For Euronorm bins, crates, boxes etc.
Design	Demountable
Base material	HDPE - plastic
Structure	2-sided / clamp frames
Wall material	Steel - hot-dip galvanised
Wheels	2 fixed and 2 swivel castors Ø 125 mm
Fork material	Steel - electrolytically galvanised
Wheel construction	Nylon rim - rubber tread (non-marking - noise-dampening)
Extra	Plastic tension straps (2)

Features

Roll container (815 x 682 x H 1710 mm) for Euronorm bins, crates and packaging

With an internal platform size of 815 x 615 mm - e.g. for 2 bins 600 x 400 mm side by side

2-sided version - usable internal height: 1500 mm

Base platform made of food-safe grey plastic

Equipped with 2 fixed and 2 swivel castors Ø 125 mm

Fitted with electrolytically galvanised wheel forks

Wheel construction: nylon rim - rubber tread (non-marking - noise-dampening - shock-absorbing)

The container is fitted with hot-dip galvanised insert walls

The walls are inserted into the container base

The hook-shaped insertion pins clamp the add-on walls securely into the container base

Locking is done by the oval drop rings

The add-on walls can also be removed again without tools

The 2-sided roll container is supplied with 2 plastic tension straps

Options: lettering - QR codes and barcodes - layer pads - coversheet - braked wheels - other wheel construction (e.g. hard nylon) - stainless steel - other wheel diameter - other container structure - folding couplings (for towing units)

Description

Grey 2-sided roll container (815 x 682 x H 1710 mm) with a usable platform size of 815 x 615 mm, suitable for Euronorm bins, crates and boxes. For example, two Euronorm bins 600 x 400 mm can fit side by side on the roll container. The roll container is fitted with a grey base platform made of food-safe plastic, equipped with smooth-running fixed and swivel castors Ø 125 mm. The forks of both the fixed and swivel castors are electrolytically galvanised. The wheels are constructed with a nylon rim fitted with a non-marking rubber tread. The version with rubber tread is particularly low-noise.

The structure of the roll container is designed with two steel clamp frames in a hot-dip galvanised finish. The side walls are inserted into the base platform and clamp themselves in place because the ends are slightly bent, creating a hook-shaped insertion pin. As a result, the add-on wall clamps itself into the base. The add-on wall is locked by the oval drop ring located in the centre of the add-on wall. When this is pushed upwards, the add-on wall can be removed from the base again. Because the clamp frames are hot-dip galvanised, they are suitable for long-term outdoor use.

The version with 2 frames is particularly practical as it can be loaded from both sides; unloading at the destination can also be done flexibly from two sides. In addition, protruding loads can be distributed to some extent. For this reason, this 2-sided version is the most commonly used design for long-term outdoor use.



Suitable accessories



Alternative articles

